HORIZONTAL BAND SAW MACHINES

Your partner for presentation of the needs



SHBM/A series

Features

- ✓ It is 4-5 times faster and Save 50%-60% electricity than hacksaws.
- ✓ Can cope with most types of material.
- ✓ Hydraulic feeding, clamp and three step adjustable.
- ✓ Blade guides with antifriction bearing and carbide pads provide precise support for the blade.
- ✓ Constructed in heavy gauge steel.
- ✓ Small material in bundle cutting device (optional).
- ✓ Driven roller table (optional)

Technical specifications

Model:	SHBM38A/38	SHBM28A/28	SHBM28A/65
Round cutting capacity	380	280	280
Square cutting capacity	380x380	630x280	280x650
Cutting speed(m/min):	30/48/62	27/46/68	30-80
Band dimensions(mm):	1.1x34x4115	1.1x34x3900	1.1x34x3900
Main Motor(kw):	3.0	3.0	3.0
Length(mm):	2050	1800	1800
Width(mm):	1150	1200	1200
Height(mm):	1500	1500	1500
Weight(KGS):	1200	1100	1200

Model:	SHBM25A/25	SHBM28A/28	SHBM38A/38	
Round cutting capacity	250	280	380	
Square cutting capacity	250x250	280x280	350x380	
Cutting speed(m/min):	25/49/81	27/49/81	27/46/68	
Band dimensions(mm):	0.9x27x3505	0.9x27x3505	1.1x34x4115	
Main Motor(kw):	2.2	2.2	3.0	
Length(mm):	1700	1900	2000	
Width(mm):	1000	1050	1100	
Height(mm):	1450	1450	1500	
Weight(KGS):	750	800	1100	

HORIZONTAL BAND SAW MACHINES

Your partner for presentation of the needs



SHBP/A series

Features

- ✓ Adopts programmable PLC with touch control screen.
- ✓ Feeding length of work piece uses grating ruler to confirm accuracy.
- ✓ All the programs can display and operate on the screen.
- ✓ English display all the information.
- ✓ The operation is simple.
- ✓ Hydraulic clamp the work piece to make it more stable.
- ✓ Automatically switch off at the end of the cut and saw frame is lifted.
- ✓ Hydraulically up to the adjusted pump.

Technical specifications

Model:	SHBP40A/25	SHBP40A/28	SHBP40A/35	SHBP40A/38	SHBP40A/28
Round cutting capacity(mm):	250	280	350	380	280
Square cutting capacity (mm):	250x250	280x280	350x350	380x380	630x280
Cutting speed(m/min):	27/49/81	27/49/81	27/46/68	27/46/68	27/46/68
Band dimensions(mm):	0.9x27x3505	0.9x27x3505	1.1x34x4115	1.1x34x4115	1.1x34x3900
Main Motor(kw):	2.2	2.2	3.0	3.0	3.0
Clamping vice:	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Blade tensioning:	Hydraulic manual	Hydraulic manual	Hydraulic manual	Hydraulic manual	Hydraulic manual
Length(mm):	1700	1900	2000	2050	1800
Width(mm):	2500	2550	2600	2650	2700
Height(mm):	1450	1450	1500	1500	1500
Weight(KGS):	970	1100	1500	1550	1500